## **Amendments to the Claims**

This listing of claims will replace all prior versions and listings of claims in the application:

## Listing of Claims

1. (Previously Presented) A flexible token, comprising:

a first member, for insertion into a Universal Serial Bus (USB)-compliant host computer female connector along a first longitudinal axis, the USB-compliant host computer female connector having a plurality of host conductive surfaces:

a second member, disposed along a second longitudinal axis, the second member having a processor providing conditional access to data stored in a memory;

a flexible conductor, electrically coupling the processor and the plurality of host conductive surfaces when the first member is inserted into the USB-compliant host computer female connector; and

a bendable member, disposed in the first longitudinal axis and coupled to the first member and the second member, the bendable member permitting the second longitudinal axis rotated away from the first longitudinal axis.

- 2. (Previously Presented) The apparatus of claim 1, wherein the bendable member comprises a joint permitting the second member to be rotated about the joint so that the second longitudinal axis is non-co-linear with the first longitudinal axis.
  - 3. (Original) The apparatus of claim 2, wherein the joint is a ball joint.

PHIP\566411\1 - 2 -

plane.

- 4. (Original) The apparatus of claim 1, wherein the bendable member comprises a hinge.
  - 5. (Original) The apparatus of claim 4, wherein: the hinge is bendable in a single plane; and

the bendable member further comprises a rotatable member permitting rotation of the

- 6. (Original) The apparatus of claim 5, wherein the bendable member comprises a gooseneck.
  - 7. (Original) The apparatus of claim 1, wherein the flexible conductor comprises: a plurality of token conductive surfaces; and

flexible wires communicatively coupled to the plurality of token conductive surfaces and the processor.

- 8. (Original) The apparatus of claim 1, wherein the flexible conductor comprises: a plurality of token conductive surfaces;
- a flex circuit, having a plurality of conductive traces coupled to the plurality of token conductive surfaces and the processor.

PHIP\566411\1 - 3 -

9. (Original) The apparatus of claim 1, wherein the flexible conductor comprises a flex circuit having:

a plurality of conductive traces communicatively coupled to the processor, the plurality of conductive traces including exposed portions presenting conductive surfaces contacting the host conductive surfaces when the first member is inserted into the USB host computer female connector.

10. (Original) The apparatus of claim 1, wherein: the token comprises a fingerprint sensor disposed on a surface of the token; and the bendable member is bendable in a plane perpendicular to the surface of the token.

## 11-19. Canceled

20. (Previously Presented) The method of claim 1, wherein the first and second members are rigid.

PHIP\566411\1 - 4 -